



#### PRODUCT DESCRIPTION

By uniting a romantic shape with a stunning circle of brilliant light, we created an Eternity™ that encapsulates a clear vision of renewal and balance, boldly illuminating your space with timeless elegance.

#### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 10-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

#### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 10-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

#### AVAILABLE OPTIONS

- Ava™ 1, 2
- Keen™ 1
- Vive™ 1, 2
- Seamless™ 1, 2
- Defogger<sup>1</sup>
- 0-10 Volt Dimming<sup>2</sup>
- Forward-phase dimming<sup>2</sup>
- 2,700K CCT<sup>2</sup>

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Calculated L<sub>70</sub> 124,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

<sup>1</sup> See technology specification sheets for more information.

<sup>2</sup> Minimum order quantity required.

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options
- Mirror can only be hung in the WxH orientation as show and is not field interchangeable

**MODELS**

Base Model*	Dimensions	Power Requirements
ETE2-21.00x30.00-EC-L7-30K	21"W x 30"H x 1.75"D (Oval) (533mm x 762mm x 44mm)	120/240 VAC, 34W
ETE2-30.00-EC-L7-30K	30" diameter x 1.75"D (762mm x 44mm)	120/240 VAC, 40W
ETE2-36.00-EC-L7-30K	36" diameter x 1.75"D (914mm x 44mm)	120/240 VAC, 51W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com)

**DIMENSIONAL DRAWING** (Not to scale. Frost and border widths may vary depending on mirror size.)

