



PRODUCT DESCRIPTION

Add glimmering light and tasteful grace to any space with a powerful impression of Integrity™. Featuring a smooth polished edge and brilliant inner frame of frosted light, this radiant marvel is as stylish as it is functional.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Ava™ SmartLook™ Technology^{1, 2}
- Keen™ SmartDim™ Technology¹
- Vive™ SmartSound™ Technology^{1, 2}
- Seamless™ SmartTime™ Technology^{1, 2}
- Night Light^{1, 2}
- Defogger¹
- Forward-phase dimming
- Diamond Clear™ DuraMirror™ glass²
- 2,700K CCT²
- Custom mirror sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Calculated L₇₀ 124,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more information.

² Minimum order quantity required.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

MODELS

Base Model*	Dimensions	Power Requirements
INT2-24.00x36.00-L7CS-30K	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 49W
INT2-30.00x42.00-L7CS-30K	30"W x 42"H x 1.75"D (762mm x 1067mm x 44mm)	120/240 VAC, 62W
INT2-36.00x36.00-L7CS-30K	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 62W
INT2-42.00x42.00-L7CS-30K	42"W x 42"H x 1.75"D (1067mm x 1067mm x 44mm)	120/240 VAC, 73W
INT2-48.00x36.00-L7CS-30K	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 73W
INT2-54.00x42.00-L7CS-30K	54"W x 42"H x 1.75"D (1372mm x 1067mm x 44mm)	120/240 VAC, 88W
INT2-60.00x36.00-L7CS-30K	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 88W
INT2-66.00x42.00-L7CS-30K	66"W x 42"H x 1.75"D (1676mm x 1067mm x 44mm)	120/240 VAC, 102W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

